


Eccentric Reducer



ASTM A403 / ANSI B16.9

Part Number	Dimensions (mm)								Weight Kg/Pce
	Nominal Pipe Size	Sch	O/D (LE)	O/D (SE)	Wall (LE)	Wall (SE)	A		
080X025EX406	3" X 1"	40s	88.9	33.4	5.49	3.38	88.9	1.00	
080X032EX406	3" X 1¼"	40s	88.9	42.2	5.49	3.56	88.9	1.00	
080X040EX406	3" X 1½"	40s	88.9	48.3	5.49	3.68	88.9	1.00	
080X050EX406	3" X 2"	40s	88.9	60.3	5.49	3.91	88.9	1.00	
080X065EX406	3" X 2½"	40s	88.9	73.0	5.49	5.16	88.9	1.00	
100X040EX406	4" X 1½"	40s	114.3	48.3	6.02	3.68	101.6	1.60	
100X050EX406	4" X 2"	40s	114.3	60.3	6.02	3.91	101.6	1.60	
100X065EX406	4" X 2½"	40s	114.3	73.0	6.02	5.16	101.6	1.60	
100X080EX406	4" X 3"	40s	114.3	88.9	6.02	5.49	101.6	1.60	
125X050EX406	5" X 2"	40s	141.3	60.3	6.55	3.91	127.0	2.75	
125X065EX406	5" X 2½"	40s	141.3	73.0	6.55	5.16	127.0	2.75	
125X080EX406	5" X 3"	40s	141.3	88.9	6.55	5.49	127.0	2.75	
125X100EX406	5" X 4"	40s	141.3	114.3	6.55	6.02	127.0	2.75	
150X050EX406	6" X 2"	40s	168.3	60.3	7.11	3.91	139.7	3.95	
150X065EX406	6" X 2½"	40s	168.3	73.0	7.11	5.16	139.7	3.95	
150X080EX406	6" X 3"	40s	168.3	88.9	7.11	5.49	139.7	3.95	
150X100EX406	6" X 4"	40s	168.3	114.3	7.11	6.02	139.7	3.95	
150X125EX406	6" X 5"	40s	168.3	141.3	7.11	6.55	139.7	3.95	
200X100EX406	8" X 4"	40s	219.1	114.3	8.18	6.02	152.4	6.50	
200X125EX406	8" X 5"	40s	219.1	141.3	8.18	6.55	152.4	6.50	
200X150EX406	8" X 6"	40s	219.1	168.3	8.18	7.11	152.4	6.50	

*Grade 316/L

*Schedule 40s Wall Thickness

*Welded Construction

*Dimensions are for guidance only – Please call to confirm if critical!