


Eccentric Reducer



ASTM A403 / ANSI B16.9

| Part Number | Dimensions (mm) | | | | | | | | Weight Kg/Pce |
|--------------|-------------------|-----|----------|----------|-----------|-----------|-------|-------|---------------|
| | Nominal Pipe Size | Sch | O/D (LE) | O/D (SE) | Wall (LE) | Wall (SE) | A | | |
| 250X100EX406 | 10" X 4" | 40s | 273.1 | 114.3 | 9.27 | 6.02 | 177.8 | 10.70 | |
| 250X150EX406 | 10" X 6" | 40s | 273.1 | 168.3 | 9.27 | 7.11 | 177.8 | 10.70 | |
| 250X200EX406 | 10" X 8" | 40s | 273.1 | 219.1 | 9.27 | 8.18 | 177.8 | 10.70 | |
| 300X150EX406 | 12" X 6" | 40s | 323.9 | 168.3 | 9.53 | 7.11 | 203.2 | 15.00 | |
| 300X200EX406 | 12" X 8" | 40s | 323.9 | 219.1 | 9.53 | 8.18 | 203.2 | 15.00 | |
| 300X250EX406 | 12" X 10" | 40s | 323.9 | 273.1 | 9.53 | 9.27 | 203.2 | 15.00 | |
| 350X200EX406 | 14" X 8" | 40s | 355.6 | 219.1 | 9.53 | 8.18 | 330.2 | 26.85 | |
| 350X250EX406 | 14" X 10" | 40s | 355.6 | 273.1 | 9.53 | 9.27 | 330.2 | 26.85 | |
| 350X300EX406 | 14" X 12" | 40s | 355.6 | 323.9 | 9.53 | 9.53 | 330.2 | 26.85 | |
| 400X200EX406 | 16" X 8" | 40s | 406.4 | 219.1 | 9.53 | 8.18 | 355.6 | 33.15 | |
| 400X250EX406 | 16" X 10" | 40s | 406.4 | 273.1 | 9.53 | 9.27 | 355.6 | 33.15 | |
| 400X300EX406 | 16" X 12" | 40s | 406.4 | 323.9 | 9.53 | 9.53 | 355.6 | 33.15 | |
| 400X350EX406 | 16" X 14" | 40s | 406.4 | 355.6 | 9.53 | 9.53 | 355.6 | 33.15 | |
| 450X250EX406 | 18" X 10" | 40s | 457.2 | 273.1 | 9.53 | 9.27 | 381.0 | 40.00 | |
| 450X300EX406 | 18" X 12" | 40s | 457.2 | 323.9 | 9.53 | 9.53 | 381.0 | 40.00 | |
| 450X350EX406 | 18" X 14" | 40s | 457.2 | 355.6 | 9.53 | 9.53 | 381.0 | 40.00 | |
| 450X400EX406 | 18" X 16" | 40s | 457.2 | 406.4 | 9.53 | 9.53 | 381.0 | 40.00 | |
| 600X300EX406 | 24" X 12" | 40s | 609.6 | 323.9 | 9.53 | 9.53 | 508.0 | 71.70 | |
| 600X350EX406 | 24" X 14" | 40s | 609.6 | 355.6 | 9.53 | 9.53 | 508.0 | 71.70 | |
| 600X400EX406 | 24" X 16" | 40s | 609.6 | 406.4 | 9.53 | 9.53 | 508.0 | 71.70 | |
| 600X450EX406 | 24" X 18" | 40s | 609.6 | 457.2 | 9.53 | 9.53 | 508.0 | 71.70 | |

*Grade 316/L

*Schedule 40s Wall Thickness

*Welded Construction

*Dimensions are for guidance only – Please call to confirm if critical!