


## Reducing Tee



## ASTM A403 / ANSI B16.9

Part Number	Dimensions (mm)								
	Nominal Pipe Size	Sch	O/D (LE)	O/D (SE)	Wall (LE)	Wall (SE)	A	B	Weight Kg/Pce
080X032TS404	3" X 1¼"	40s	88.9	42.2	5.49	3.56	86	70	2.04
080X040TS404	3" X 1½"	40s	88.9	48.3	5.49	3.69	86	73	2.05
080X050TS404	3" X 2"	40s	88.9	60.3	5.49	3.91	86	76	2.16
080X065TS404	3" X 2½"	40s	88.9	73.0	5.49	5.16	86	83	2.29
100X040TS404	4" X 1½"	40s	114.3	48.3	6.02	3.69	105	86	3.41
100X050TS404	4" X 2"	40s	114.3	60.3	6.02	3.91	105	89	3.52
100X065TS404	4" X 2½"	40s	114.3	73.0	6.02	5.16	105	95	3.70
100X080TS404	4" X 3"	40s	114.3	88.9	6.02	5.49	105	98	3.83
125X050TS404	5" X 2"	40s	141.3	60.3	6.55	3.91	124	105	5.58
125X065TS404	5" X 2½"	40s	141.3	73.0	6.55	5.16	124	108	5.65
125X080TS404	5" X 3"	40s	141.3	88.9	6.55	5.49	124	111	5.71
125X100TS404	5" X 4"	40s	141.3	114.3	6.55	6.02	124	117	6.14
150X065TS404	6" X 2½"	40s	168.3	73.0	7.11	5.16	143	121	8.40
150X080TS404	6" X 3"	40s	168.3	88.9	7.11	5.49	143	124	8.52
150X100TS404	6" X 4"	40s	168.3	114.3	7.11	6.02	143	130	8.81
150X125TS404	6" X 5"	40s	168.3	141.3	7.11	6.55	143	137	9.21
200X100TS404	8" X 4"	40s	219.1	114.3	8.18	6.02	178	156	15.90
200X125TS404	8" X 5"	40s	219.1	141.3	8.18	6.55	178	162	16.30
200X150TS404	8" X 6"	40s	219.1	168.3	8.18	7.11	178	168	16.80

\*Grade 304/L

\*Schedule 40s Wall Thickness

\*Seamless Construction

\*Dimensions are for guidance only – Please call to confirm if critical!